



Grade:	GJ
Description:	An overprintable holographic foil for application at a low temperatures.
Main characteristics:	Suitable for use on a wide range of substrates giving a high gloss finish. Offers a high surface tension of 40–44 dynes, which gives good results when overprinting and varnishing.
Fields of application:	Packaging for cosmetics, wine & spirit cartons as well as greeting cards.
Definition:	Medium to solid.
Stamping method:	Platen & Cylinder
Working temperature:	Platen 100 – 140 °C Cylinder 130 – 170 °C
Manufactured widths:	750mm

This should just be used as guidance due to the fact that the temperature is directly related to speed of machinery.

Please note that this information should be used as a guide only and not as a guarantee of suitability due to the wide variety of substrates and working methods used. We would recommend that a foil sample is tested prior to purchase. We endeavour to keep our foils in stock however please be advised that stock levels do fluctuate depending on demand and we therefore recommend that you contact the office for up to date stock information prior to ordering.

Product Data Sheet V.1.0.1

Date Issued 23.03.2021

Office Controlled

Foilco
Enterprise Way
Lowton St Mary's
Warrington
Cheshire
WA3 2BP
United Kingdom

Phone +44 (0) 1942 262 622
Enquiries hello@foilco.com
Twitter foilco
Instagram foilcoltd
Visit foilco.com

