



Grade:	KMS
Description:	An over-printable gloss pigment foil for the graphics industry.
Main characteristics:	High gloss, suitable for a wide range of coated & uncoated paper/board, film laminates, polycarbonate, flexible & rigid PVC.
Fields of application:	Packaging & labels for cosmetics, wine & spirits cartons.
Definition:	Fine to medium.
Stamping method:	Vertical, Platen, Cylinder and Rotary
Working temperature:	Vertical 100 – 130 °C Platen 100 – 130 °C Cylinder 130 – 160 °C Rotary 150 – 210 °C

This should just be used as guidance due to the fact that the temperature is directly related to speed of machinery.

Manufactured widths: 610mm

Please note that this information should be used as a guide only and not as a guarantee of suitability due to the wide variety of substrates and working methods used. We would recommend that a foil sample is tested prior to purchase. We endeavour to keep our foils in stock however please be advised that stock levels do fluctuate depending on demand and we therefore recommend that you contact the office for up to date stock information prior to ordering.

Product Data Sheet V.1.0.1

Date Issued 23.03.2021

Office Controlled

Foilco
Enterprise Way
Lowton St Mary's
Warrington
Cheshire
WA3 2BP
United Kingdom

Phone +44 (0) 1942 262 622
Enquiries hello@foilco.com

Twitter foilco
Instagram foilcoltd

Visit foilco.com



Certificate No. Q09087