



<b>Grade:</b>	NAB
<b>Description:</b>	A scratch & rub resistant matt black foil for the graphics sector.
<b>Main characteristics:</b>	A matt foil specifically designed to not rub. Especially useful on high value brands where light coloured papers are used and the foil rubbing would look unsightly. Very good foil for providing fine detail amongst larger printing areas. Suitable for ABS, acetate, acrylic, polyester, polyurethane, pyroxlin and rigid PVC. Bookcloth, coated leather, coated and uncoated paper. Parchment, aqueous and UV coated stocks. Most inks and laminates. Lacquered wood and satin ribbon.
<b>Fields of application:</b>	Self adhesive labels, flat sheet labels, magazines, packaging for cosmetics, wine & spirit boxes, greeting cards & giftwrap.
<b>Definition:</b>	Medium to solid.
<b>Stamping method:</b>	Vertical, Platen, Cylinder & Rotary
<b>Working temperature:</b>	Vertical 110 – 150 °C Platen 110 – 150 °C Cylinder 130 – 170 °C Rotary 150 – 210 °C
<i>This should just be used as guidance due to the fact that the temperature is directly related to speed of machinery.</i>	
<b>Manufactured widths:</b>	610mm

*Please note that this information should be used as a guide only and not as a guarantee of suitability due to the wide variety of substrates and working methods used. We would recommend that a foil sample is tested prior to purchase. We endeavour to keep our foils in stock however please be advised that stock levels do fluctuate depending on demand and we therefore recommend that you contact the office for up to date stock information prior to ordering.*

Product Data Sheet V.1.0.1

Date Issued 23.03.2021

Office Controlled

Foilco  
Enterprise Way  
Lowton St Mary's  
Warrington  
Cheshire  
WA3 2BP  
United Kingdom

Phone +44 (0) 1942 262 622  
Enquiries hello@foilco.com  
Twitter foilco  
Instagram foilcoltd  
Visit foilco.com



Certificate No. Q09087