



Grade:	BA
Description:	A gloss pigment foil on 15 micron polyester for the plastics industry.
Main characteristics:	Very high gloss, suitable for a wide range of plastics. Styrenes, polyethylene, PVC & PMMA. Resists attack by many consumer chemicals such as alcohol, perfume, shampoo, hand lotion, etc. Excellent scratch & rub resistance
Fields of application:	Cosmetics, point of sale, extrusion.
Definition:	Medium but can achieve fine detail
Stamping method:	Vertical & Rotary
Working temperature:	Vertical 170 – 210 °C Rotary 130 – 200 °C

This should just be used as guidance due to the fact that the temperature is directly related to speed of machinery.

Manufactured widths: 695mm

Please note that this information should be used as a guide only and not as a guarantee of suitability due to the wide variety of substrates and working methods used. We would recommend that a foil sample is tested prior to purchase. We endeavour to keep our foils in stock however please be advised that stock levels do fluctuate depending on demand and we therefore recommend that you contact the office for up to date stock information prior to ordering.

Product Data Sheet V.1.0.2

Date Issued 03.07.2023

Office Controlled

Foilco
Enterprise Way
Lowton St Mary's
Warrington
Cheshire
WA3 2BP
United Kingdom

Phone +44 (0) 1942 262 622
Enquiries hello@foilco.com

Twitter foilco
Instagram foilcoltd

Visit foilco.com

