



<b>Grade:</b>	CGX
<b>Description:</b>	A unique foil suitable for scratch off application.
<b>Main characteristics:</b>	Suitable for coated board, laminated board and various plastics. The foil offers a hot stamping alternative to scratch off application where superior hiding is required. Manufactured on 15 micron polyester carrier.
<b>Fields of application:</b>	Paper, labels & card stocks.
<b>Definition:</b>	Solid
<b>Stamping method:</b>	Platen & Cylinder
<b>Working temperature:</b>	Platen 95 – 120 °C Cylinder 95 – 120 °C

*This should just be used as guidance due to the fact that the temperature is directly related to speed of machinery.*

**Manufactured widths:** 610mm

*Please note that this information should be used as a guide only and not as a guarantee of suitability due to the wide variety of substrates and working methods used. We would recommend that a foil sample is tested prior to purchase. We endeavour to keep our foils in stock however please be advised that stock levels do fluctuate depending on demand and we therefore recommend that you contact the office for up to date stock information prior to ordering.*

Product Data Sheet V.1.0.2

Date Issued 05.07.2023

Office Controlled

Foilco  
Enterprise Way  
Lowton St Mary's  
Warrington  
Cheshire  
WA3 2BP  
United Kingdom

Phone +44 (0) 1942 262 622  
Enquiries hello@foilco.com  
Twitter foilco  
Instagram foilcoltd  
Visit foilco.com

