



Grade:	EB
Description:	A foil specially formulated for use on medium density fiberboard, real wood as well as some grades of particleboard and hardboard.
Main characteristics:	These foils feature a clean release, excellent adhesion and with a top coat for exceptional protection against marring, scratching and abrasion. Decorative and functional, the foils can be applied on flat surfaces, profile or contour edges.
Fields of application:	Furniture, kitchen cabinets, trophy/award plaques, doors, mouldings and flooring.
Chemical resistance:	Lemon juice, mustard, mineral oil, coffee, cola, beer, wine, water, alcohol, lipstick, detergent, furniture polish.
Stamping method:	Silicone roller 60 – 80 durometer
Working temperature:	Transfer Temperature 165 – 200 °C

This should just be used as guidance due to the fact that the temperature is directly related to speed of machinery.

Please note that this information should be used as a guide only and not as a guarantee of suitability due to the wide variety of substrates and working methods used. We would recommend that a foil sample is tested prior to purchase. We endeavour to keep our foils in stock however please be advised that stock levels do fluctuate depending on demand and we therefore recommend that you contact the office for up to date stock information prior to ordering.

Product Data Sheet V.1.0.2

Date Issued 03.07.2023

Office Controlled

Foilco
Enterprise Way
Lowton St Mary's
Warrington
Cheshire
WA3 2BP
United Kingdom

Phone +44 (0) 1942 262 622
Enquiries hello@foilco.com
Twitter foilco
Instagram foilcoltd
Visit foilco.com

