



Grade:	LK
Description:	A high gloss metallic foil for the plastics sector.
Main characteristics:	Suitable for a wide range of plastics, especially good on PP. Provides excellent abrasion resistance as well as providing resistance to water, alcohol, & various chemicals.
Fields of application:	Cosmetic and industrial plastic components.
Definition:	Medium.
Stamping method:	Vertical & Platen
Working temperature:	Metal Die 135 – 160 °C Platen 175 – 200 °C
<i>This should just be used as guidance due to the fact that the temperature is directly related to speed of machinery.</i>	
Manufactured widths:	640mm

Please note that this information should be used as a guide only and not as a guarantee of suitability due to the wide variety of substrates and working methods used. We would recommend that a foil sample is tested prior to purchase. We endeavour to keep our foils in stock however please be advised that stock levels do fluctuate depending on demand and we therefore recommend that you contact the office for up to date stock information prior to ordering.

Product Data Sheet V.1.0.2

Date Issued 03.07.2023

Office Controlled

Foilco
Enterprise Way
Lowton St Mary's
Warrington
Cheshire
WA3 2BP
United Kingdom

Phone +44 (0) 1942 262 622
Enquiries hello@foilco.com

Twitter foilco
Instagram foilcoltd

Visit foilco.com

