



|                               |   |
|-------------------------------|---|
| <b>Grade:</b>                 | LNL   |
| <b>Description:</b>           | A general purpose matt pigment foil.  |
| <b>Main characteristics:</b>  | Suitable on a wide range of substrates with excellent versatility. Very good for reversed out areas. It has a good opacity and can be overprinted. An excellent foil for a variety of laminated, coated & uncoated papers & boards. |
| <b>Fields of application:</b> | Coated and uncoated papers and boards, labels, cartons, woven ribbons, napkins, bookbinding cloths, leather goods, wood (plain & lacquered), pipe marking, & date coding.   |
| <b>Definition:</b>            | Fine to Solid.  |
| <b>Stamping method:</b>       | Vertical, Platen & Cylinder   |
| <b>Working temperature:</b>   | Vertical            90 – 130 °C<br>Platen             90 – 130 °C<br>Cylinder          140 – 180 °C   |

*This should just be used as guidance due to the fact that the temperature is directly related to speed of machinery.*

**Manufactured widths:** 762mm

*Please note that this information should be used as a guide only and not as a guarantee of suitability due to the wide variety of substrates and working methods used. We would recommend that a foil sample is tested prior to purchase. We endeavour to keep our foils in stock however please be advised that stock levels do fluctuate depending on demand and we therefore recommend that you contact the office for up to date stock information prior to ordering.*

Product Data Sheet V.1.0.3

Date Issued 03.07.2023

Office Controlled

Foilco  
Enterprise Way  
Lowton St Mary's  
Warrington  
Cheshire  
WA3 2BP  
United Kingdom

Phone +44 (0) 1942 262 622  
Enquiries hello@foilco.com  
  
Twitter foilco  
Instagram foilcoltd  
  
Visit foilco.com

