



Grade:	SH
Description:	A metallic sheen foil for the graphics sector.
Main characteristics:	A versatile foil where combination stamping is necessary, high heat and pressure can be achieved without distortion. Very good foil for providing fine detail amongst larger printing areas. Suitable for ABS, acetate, acrylic, polyester, polyurethane, pyroxlin and rigid PVC. Bookcloth, coated leather, coated and uncoated paper. Parchment, aqueous and UV coated stocks. Most inks and laminates. Lacquered wood and satin ribbon.
Fields of application:	Self adhesive labels, flat sheet labels, magazines, packaging for cosmetics, wine & spirit boxes, greeting cards & giftwrap.
Definition:	Medium.
Stamping method:	Vertical, Platen, Cylinder & Rotary
Working temperature:	Vertical 110 – 150 °C Platen 110 – 150 °C Cylinder 130 – 170 °C Rotary 150 – 210 °C

This should just be used as guidance due to the fact that the temperature is directly related to speed of machinery.

Manufactured widths: 610mm & 1220mm

Not all colours are held in these widths

Please note that this information should be used as a guide only and not as a guarantee of suitability due to the wide variety of substrates and working methods used. We would recommend that a foil sample is tested prior to purchase. We endeavour to keep our foils in stock however please be advised that stock levels do fluctuate depending on demand and we therefore recommend that you contact the office for up to date stock information prior to ordering.

Product Data Sheet V.1.0.2

Date Issued 05.07.2023

Office Controlled

Foilco
Enterprise Way
Lowton St Mary's
Warrington
Cheshire
WA3 2BP
United Kingdom

Phone +44 (0) 1942 262 622
Enquiries hello@foilco.com
Twitter foilco
Instagram foilcoltd
Visit foilco.com

