FOILCO

Grade:	AAN	
Description:	A general purpose gloss pigment foil for the graphics sector.	
Main characteristics:	Suitable for a wide range of coated & film laminated boards as well as polystyrene, polyurethane, polycarbonate, acetate, acrylic, coated leather and rigid PVC.	
Fields of application:	Cosmetic labels, packaging & greeting cards.	
Definition:	Fine to Medium	
Stamping method:	Vertical, Platen, Cylinder & Rotary	
Working temperature:	Vertical	100 – 130 °C
	Platen	90 – 130 °C
	Cylinder	130 – 160 °C
	Rotary	150 – 210 °C

This should just be used as guidance due to the fact that the temperature is directly related to speed of machinery.

Manufactured widths:	640mm
Manufactured thickness:	12 Micron Polyester

Please note that this information should be used as a guide only and not as a guarantee of suitability due to the wide variety of substrates and working methods used. We would recommend that a foil sample is tested prior to purchase. We endeavour to keep our foils in stock however please be advised that stock levels do fluctuate depending on demand and we therefore recommend that you contact the office for up to date stock information prior to ordering.

Address:

Foilco Limited
Enterprise Way
Lowton St Mary's
Warrington, Cheshire
WA3 2BP
United Kingdom

Phone: +44 (0) 1942 262622
Enquiries: hello@foilco.com

LinkedIn: foilcoltd
Twitter: foilco
Instagram: foilcoltd

Website: www.foilco.com

Company No. 2140459 / VAT Reg. No. GB 468117042

Certified B Corporation Learn more at bcorp.com

bsi ISO 9001 Quality Management Systems CERTIFIED Q 09087 ISO 14001 Environmental Management CERTIFIED EMS 724693

ZERO FOIL TO LANDFILL