



Grade:	NZ								
Description:	A general purpose gloss pigment foil for the plastics sector.								
Main characteristics:	Suitable for a wide range of plastics such as ABS, polypropylene and polystyrene. Also suitable for filmic labels.								
Fields of application:	Picture frames, packaging, cosmetic tubes, point of sale.								
Definition:	Fine to Medium.								
Stamping method:	Vertical, Platen, Cylinder & Rotary								
Working temperature:	<table><tr><td>Vertical</td><td>100 – 130 °C</td></tr><tr><td>Platen</td><td>100 – 130 °C</td></tr><tr><td>Cylinder</td><td>130 – 160 °C</td></tr><tr><td>Rotary</td><td>150 – 210 °C</td></tr></table>	Vertical	100 – 130 °C	Platen	100 – 130 °C	Cylinder	130 – 160 °C	Rotary	150 – 210 °C
Vertical	100 – 130 °C								
Platen	100 – 130 °C								
Cylinder	130 – 160 °C								
Rotary	150 – 210 °C								

This should just be used as guidance due to the fact that the temperature is directly related to speed of machinery.

Manufactured widths:	610mm
Manufactured thickness:	12 Micron Polyester

Please note that this information should be used as a guide only and not as a guarantee of suitability due to the wide variety of substrates and working methods used. We would recommend that a foil sample is tested prior to purchase. We endeavour to keep our foils in stock however please be advised that stock levels do fluctuate depending on demand and we therefore recommend that you contact the office for up to date stock information prior to ordering.

Product Data Sheet V.1.0.5

Date Issued 27.08.2026

Office Controlled

Address:

Foilco Limited
Enterprise Way
Lowton St Mary's
Warrington, Cheshire
WA3 2BP
United Kingdom

Phone: +44 (0) 1942 262622
Enquiries: hello@foilco.com

LinkedIn: foilcoltd
Twitter: foilco
Instagram: foilcoltd
Website: www.foilco.com

Company No. 2140459 / VAT Reg. No. GB 468117042

